

SolidBank® 601 Office VoIP 10

Digital voice recorder

for Voice over IP extensions



Automatic operation	Automatically records communication.
Lots of data	Up to 6.250 hours of data, depending on compression.
Remote management	Status and error signals are accessible via a web interface.
Alarm	SNMP capability.
Authorizing system	Multi level system with protection against unauthorized access.
Logging	Logs functions and user actions.
Service and support	Service and support.
Easy archiving	By using the optional FTP client.



From small- and medium-sized enterprises to big companies, from private sector and public organizations to armed forces and special services, now everyone can find the optimal digital voice recorder for their needs in the **SolidBank® 601** product family.

By utilizing the members of the product family, recording and retrieving transactions are simple and effective. The unique hardware and software elements provide the maximum safety for all recorded data. All information hidden in calls is saved for the long-term; it can be replayed any time and can be used for any purpose from recording essential business data, to collecting marketing information or improving the quality of your workflow.

If required, complex DSR SolidLog® systems can be constructed by linking several voice recorders. For these systems we provide archiving and improved data-storage solutions.

SolidBank® 601 Office VoIP 10 has been developed for recording Voice over IP signal sources from virtually all PBXs using port-mirroring technology.



Recording

Comprehensive connections - the device can record VoIP communication of virtually all known PBXs (Cisco, Avaya, Alcatel, Ericsson, Panasonic, Siemens, Nortel, Asterisk).

Sufficient capacity - the device can record the communication of 10 VoIP channels in one small and state of the art device. It is ideal for small and medium-sized companies.

Voice documenting - storing additional data besides records, by which important information is recoverable and it is easier to retrieve certain conversations.



Replaying

Accessibility - recorded calls and call-information can be accessed and managed by using a client-application or through the web by using a common browser.

Flexible search - by using the stored additional information, it is possible to implement aimed search and with the help of specified parameters records can be filtered and listed as well. Filter conditions can be combined on demand to assist aimed search.

Exporting - after taking safety issues into consideration recorded data can be saved in several formats, enclosed and sent as an attachment; or published on the web.

Safety - this multi-level, flexible authorizing system can prevent unauthorized access. Every user is permitted to accomplish only pre-determined working processes.

SolidBank® 601 Office VoIP 10

Digital voice recorder
for Voice over IP extensions



Voice recording specification

Simultaneously recordable channels	• 10 (pre-configured, can not be modified)
Recordable signal sources	• Cisco (Skinny) • Avaya (H.323) • Alcatel (H.323) • Ericsson (H.323) • Panasonic (H.323) • Siemens (CorNet IP) • Nortel (H.323) • Asterisk (SIP)
Startup	• automatic
Storage media	• 3,5" HDD
Storage format	• G.711 (uncompressed) • G.723 (compressed, 2 x 6,3 Kbit/s) • G.729, G.729A (compressed, 2 x 8 Kbit/s)
Storage capacity	• G.711 (uncompressed): 625 h • G.723 (compressed): 6.250 h • G.729 (compressed): 5.000 h
Listing, replaying	10/100 Base-T Ethernet: • web interface client application • DSR EasyReplay application
Auxiliary information to help retrieving	• starting time • length of call • calling and called phone number • name associated to extension • call direction • coding
Save records to workstation	• by using a browser • by using DSR EasyReplay client
Alarm	• via the web interface • via SNMP

Technical data

Power	100-240 V AC, 2A, 50-60 Hz (external AC/DC adapter, DC12V/0.8 A)
Power consumption	35 W
Mechanical finish	compact, desktop build
Dimensions	ITX, 220 mm wide, 321 mm deep x 60 mm high
Temperature	operating: +5...+35 °C / storage: -30...+60 °C
Humidity	operating: 10...90 % RH / storage: 5...95 % RH
Change of temperature	operating: max. 20 °C/h / storage: max. 30 °C/h



Office: H-1117 Budapest, Prielle Kornélia u. 19/G
Tel.: +36 1 464 4380 • Fax: +36 1 371 1788 • e-mail: support@dsr.hu



www.dsr.hu

DSR Ltd. reserves the right to make modifications.